

HIGEN		INDUCTION MOTOR DATA SHEET		0.4 kW - 4 P	
MODEL: KMI-400V6F		CUSTOMER :		REV. NO :	
APPLICATION:		PROJECT NAME:		QUANTITY :	
GENERAL DATA			PERFORMANCE DATA		
FRAME NO.		FF130		OUTPUT 0.4 kW	
ENCLOSURE	<input type="checkbox"/> DRIP PROOF		POLES 4 POLES		
	<input checked="" type="checkbox"/> TOTALLY ENCLOSED		ROTOR TYPE SQUIRREL CAGE		
	<input type="checkbox"/> Increased Safety Exp.-proof		STARTING METHOD <input checked="" type="checkbox"/> D.O.L <input type="checkbox"/> Y-		
PROTECTION	IP 44		<input type="checkbox"/> REACTOR (%TAP) <input type="checkbox"/> V.V.V.F		
METHODS OF COOLING	<input type="checkbox"/> SC <input checked="" type="checkbox"/> FC <input type="checkbox"/>		<input type="checkbox"/> SOFT-STARTER		
FREQUENCY	60 Hz		RATED VOLTAGE 440 V V V		
PHASE	3 PHASE		CURRENT		
SERVICE FACTOR	1.15		NO LOAD A A A		
INSULATION CLASS	B CLASS		FULL LOAD 1.1 A A A		
TEMP. RISE AT FULL LOAD (at S.F 1.0)			STARTING 7.2 A A A		
RES. METHOD		85		EFFICIENCY	
THERMO. METHOD				AT 1/2 LOAD %	
LOCATION	<input checked="" type="checkbox"/> INDOOR <input type="checkbox"/> OUTDOOR		AT 3/4 LOAD %		
ALTITUDE	1000 m		AT FULL LOAD 75.0 %		
HUMIDITY	80 %		POWER FACTOR		
AMBIENT TEMPERATURE	-10~40		AT 1/2 LOAD %		
RATING	<input checked="" type="checkbox"/> CONT. <input type="checkbox"/> %ED		AT 3/4 LOAD %		
NEMA DESIGN	V		AT FULL LOAD 63.0 %		
MOUNTING	<input type="checkbox"/> B3 <input type="checkbox"/> B5 <input checked="" type="checkbox"/> V1 <input type="checkbox"/> B3B5		SPEED (AT FULL LOAD)		1710 rpm
BEARING	TYPE	BALL		TORQUE	
	DEW-DE	6203ZZ/6203ZZ		FULL LOAD 0.2 kg-m 100%	
	LUBRICANT	GREASE		LOCKED ROTOR 0.4 kg-m 200%	
COUPLING METHOD		<input checked="" type="checkbox"/> DIRECT <input type="checkbox"/> V-BELT		BREAKDOWN 0.4 kg-m 200%	
SHAFT		NOISE LEVEL		61.0 dB(A)	
EXTENSION		SINGLE		VIBRATION 15.0 μ m	
EXTERNAL THRUST		ALLOWABLE LOAD GD ² REFERRED TO MOTOR SHAFT			
TERMINAL BOX		(AT DIRECT ON-LINE)		2.4 kg-m ²	
MAIN		<input checked="" type="checkbox"/> STEEL <input type="checkbox"/> AL <input type="checkbox"/> CAST		Motor GD ² 0.0079 kg-m ²	
AUX.		<input type="checkbox"/> YES <input checked="" type="checkbox"/> NO		MOTOR APPROX. WEIGHT 13.0 kg	
BOX LOCATION		LEFT (Viewed from Drive end)		PAINTING	MUNSELL NO. 7.1B4.0/0.9
APPLICATION STANDARDS		IEC, KS		THICKNESS	<input checked="" type="checkbox"/> STANDARD <input type="checkbox"/> μ m
ACCESSORIES (OPTIONAL)			SUBMITTAL DRAWINGS		
NOTE		REMARKS			
1. THESE DATA ARE ONLY DESIGN VALUES AND SHALL BE GUARANTEED WITH TOLERANCE OF APPLICATION STANDARDS.		1. ABOVE ALL DATA ARE CALCULATED AT 100% VOLTAGE.			
2. OTHERS NOT MENTIONED IN THIS SHEET SHALL BE IN ACCORDANCE WITH OTIS STANDARD.					
FC : FAN COOLED	SC : SELF COOLED	DATE	PREPARED	CHECKED	APPROVED
		2007.11.13	M.S.PARK	H.K.KIM	H.J.KIM