

HIGEN		INDUCTION MOTOR DATA SHEET		2.2 kW - 4 P	
MODEL: KMI-03HQ6		CUSTOMER :		REV. NO :	
APPLICATION:		PROJECT NAME:		QUANTITY : SETS	
GENERAL DATA		PERFORMANCE DATA			
FRAME NO.	100L	OUTPUT	2.2 kW		
ENCLOSURE	<input type="checkbox"/> DRIP PROOF	POLES	4 POLES		
	<input checked="" type="checkbox"/> TOTALLY ENCLOSED	ROTOR TYPE	SQUIRREL CAGE		
	<input type="checkbox"/> Increased Safety Exp.-proof	STARTING METHOD	<input checked="" type="checkbox"/> D.O.L <input type="checkbox"/> Y-		
PROTECTION	IP 44		<input type="checkbox"/> REACTOR (%TAP) <input type="checkbox"/> V.V.V.F		
METHODS OF COOLING	<input type="checkbox"/> SC <input checked="" type="checkbox"/> FC <input type="checkbox"/> DP		<input type="checkbox"/> VECTOR DRIVE		
PHASE	3 PHASE	RATED VOLTAGE	380 V	V	V
SERVICE FACTOR	1.0	FREQUENCY	50 Hz		
INSULATION CLASS	B CLASS	CURRENT			
TEMP. RISE AT FULL LOAD (at S.F 1.0)		NO LOAD	A	A	A
RES. METHOD	85	FULL LOAD	5.6 A	A	A
THERMO. METHOD		STARTING	36.2 A	A	A
LOCATION	<input checked="" type="checkbox"/> INDOOR <input type="checkbox"/> OUTDOOR	EFFICIENCY			
ALTITUDE	1000 m	AT 1/2 LOAD	%		
HUMIDITY	80 %	AT 3/4 LOAD	%		
AMBIENT TEMPERATURE	-10~40	AT FULL LOAD	78.0	%	
RATING	<input checked="" type="checkbox"/> CONT. <input type="checkbox"/> %ED	POWER FACTOR			
NEMA DESIGN	B	AT 1/2 LOAD	%		
MOUNTING	<input checked="" type="checkbox"/> B3 <input type="checkbox"/> B5 <input type="checkbox"/> V1 <input type="checkbox"/> B3B5	AT 3/4 LOAD	%		
BEARING	TYPE	AT FULL LOAD	77.0	%	
	DEW-DE	6206ZZ/6205ZZ	SPEED (AT FULL LOAD)		
	LUBRICANT	GREASE	1430 rpm		
COUPLING METHOD	<input checked="" type="checkbox"/> DIRECT <input type="checkbox"/> V-BELT	TORQUE			
ROTATION(Facing Drive End)	<input checked="" type="checkbox"/> CW <input checked="" type="checkbox"/> CCW	FULL LOAD	1.5	kg-m	100%
SHAFT	EXTENSION	LOCKED ROTOR	2.7	kg-m	180%
		BREAKDOWN	3.0	kg-m	200%
		NOISE LEVEL	68	dB(A)	
EXTERNAL THRUST		VIBRATION	30.0	μm	
TERMINAL BOX		ALLOWABLE LOAD GD ² REFERRED TO MOTOR SHAFT			
MAIN	<input checked="" type="checkbox"/> STEEL <input type="checkbox"/> AL <input type="checkbox"/> CAST	(AT DIRECT ON-LINE)	12.0	kg-m ²	
AUX.	<input type="checkbox"/> YES <input checked="" type="checkbox"/> NO	Motor GD ²	0.0351	kg-m ²	
BOX LOCATION	LEFT (Viewed from Drive end)	MOTOR APPROX. WEIGHT	32	kg	
APPLICATION STANDARDS	KS.IEC	PAINTING	MUNSELL NO.	7.1B4/0.9	
		THICKNESS	<input checked="" type="checkbox"/> STANDARD <input type="checkbox"/>	μm	
ACCESSORIES (OPTIONAL)		SUBMITTAL DRAWINGS			
NOTE		REMARKS			
1. THESE DATA ARE ONLY DESIGN VALUES AND SHALL BE		1. ABOVE ALL DATA ARE CALCULATED AT 100% VOLTAGE.			
GUARANTEED WITH TOLERANCE OF APPLICATION STANDARDS.					
2. OTHERS NOT MENTIONED IN THIS SHEET SHALL BE					
IN ACCORDANCE WITH HIGEN STANDARD.					
TE : TOTALLY ENCLOSED	DP : DRIP PROOF	DATE	PREPARED	CHECKED	APPROVED
FC : FAN COOLED	SC : SELF COOLED	2009-04-13	H.Y.KIM	H.J.KIM	H.J.KIM