

HIGEN		INDUCTION MOTOR DATA SHEET		5 HP - 2 P	
MODEL: KMI-05HK3		CUSTOMER :		REV. NO : 0	
APPLICATION:		PROJECT NAME:		QUANTITY : SETS	
GENERAL DATA			PERFORMANCE DATA		
FRAME NO.		112M		OUTPUT 3.7 kW 5 HP	
ENCLOSURE	<input type="checkbox"/> DRIP PROOF		POLES 2 POLES		
	<input checked="" type="checkbox"/> TOTALLY ENCLOSED		ROTOR TYPE SQUIRREL CAGE		
	<input type="checkbox"/> Increased Safety Exp.-proof		STARTING METHOD <input checked="" type="checkbox"/> D.O.L <input type="checkbox"/> Y-		
PROTECTION	IP 44		<input type="checkbox"/> REACTOR (%TAP) <input type="checkbox"/> V.V.V.F		
METHODS OF COOLING	<input type="checkbox"/> SC <input checked="" type="checkbox"/> FC <input type="checkbox"/> AO		<input type="checkbox"/> SOFT-STARTER		
FREQUENCY	60 Hz		RATED VOLTAGE 220 V 380 V V		
PHASE	3 PHASE		CURRENT		
SERVICE FACTOR	1.15		NO LOAD A A A		
INSULATION CLASS	F CLASS		FULL LOAD 13.0 A 7.5 A A		
TEMP. RISE AT FULL LOAD (at S.F 1.0)			STARTING 118.2 A 68.4 A A		
RES. METHOD		100		EFFICIENCY	
THERMO. METHOD				AT 1/2 LOAD %	
LOCATION	<input checked="" type="checkbox"/> INDOOR <input type="checkbox"/> OUTDOOR		AT 3/4 LOAD %		
ALTITUDE	1000 m		AT FULL LOAD 84.0 %		
HUMIDITY	90 %		POWER FACTOR		
AMBIENT TEMPERATURE	-10~40		AT 1/2 LOAD %		
RATING	<input checked="" type="checkbox"/> CONT. <input type="checkbox"/> %ED		AT 3/4 LOAD %		
NEMA DESIGN	B		AT FULL LOAD 89.0 %		
MOUNTING	<input checked="" type="checkbox"/> B3 <input type="checkbox"/> B5 <input type="checkbox"/> V1 <input type="checkbox"/> B3B5		SPEED (AT FULL LOAD) 3520 rpm		
BEARING	TYPE	BALL		TORQUE	
	DEW-DE	6206ZZ/6205ZZ		FULL LOAD 1.0 kg-m 100%	
	LUBRICANT			LOCKED ROTOR 1.6 kg-m 160%	
COUPLING METHOD		<input checked="" type="checkbox"/> DIRECT <input type="checkbox"/> V-BELT		BREAKDOWN 2.0 kg-m 200%	
SHAFT			NOISE LEVEL 80.0 dB(A)		
EXTENSION		SINGLE		VIBRATION 30.0 μm	
EXTERNAL THRUST		ALLOWABLE LOAD GD ² REFERRED TO MOTOR SHAFT			
TERMINAL BOX			(AT DIRECT ON-LINE) 3.3 kg-m ²		
MAIN		<input checked="" type="checkbox"/> STEEL <input type="checkbox"/> AL <input type="checkbox"/> CAST		Motor GD ² 0.05700 kg-m ²	
AUX.		<input type="checkbox"/> YES <input checked="" type="checkbox"/> NO		MOTOR APPROX. WEIGHT 42.0 kg	
BOX LOCATION		LEFT (Viewed from Drive end)		PAINTING	MUNSELL NO. 7.1 B 4.0/0.9
APPLICATION STANDARDS		KS.IEC		THICKNESS	<input checked="" type="checkbox"/> STANDARD <input type="checkbox"/> μm
ACCESSORIES (OPTIONAL)			SUBMITTAL DRAWINGS		
TEMPERATURE DETECTOR			OUTLINE DIMENSION DW-H-112M-CA		
WINDING		Main Terminal Box TB-3M95996			
TYPE		Speed Vs Torque, current Curve ST-KMI-05HK3			
BEARING					
TYPE					
SPACE HEATER					
RATING					
NOTE			REMARKS		
1. THESE DATA ARE ONLY DESIGN VALUES AND SHALL BE GUARANTEED WITH TOLERANCE OF APPLICATION STANDARDS.			1. ABOVE ALL DATA ARE CALCULATED AT 100% VOLTAGE.		
2. OTHERS NOT MENTIONED IN THIS SHEET SHALL BE IN ACCORDANCE WITH OTIS-LG STANDARD.					
TE : TOTALLY ENCLOSED		DP : DRIP PROOF		DATE	PREPARED
FC : FAN COOLED		SC : SELF COOLED		2005-11-09	H.G.HAN
				CHECKED	APPROVED
				H.J.KIM	H.T.KIM