

HIGEN		INDUCTION MOTOR DATA SHEET		25 HP - 4 P	
MODEL: KMH-25HC1		CUSTOMER :		REV. NO : 0	
APPLICATION:		PROJECT NAME:		QUANTITY : SETS	
GENERAL DATA			PERFORMANCE DATA		
FRAME NO.		180M		OUTPUT 18.5 kW 25 HP	
ENCLOSURE		<input type="checkbox"/> DRIP PROOF		POLES 4 POLES	
		<input checked="" type="checkbox"/> TOTALLY ENCLOSED		ROTOR TYPE SQUIRREL CAGE	
		<input type="checkbox"/> Increased Safety Exp.-proof		<input type="checkbox"/> D.O.L <input checked="" type="checkbox"/> Y- <input type="checkbox"/> REACTOR ( %TAP) <input type="checkbox"/> V.V.V.F <input type="checkbox"/> SOFT-STARTER	
PROTECTION		IP 54		STARTING METHOD	
METHODS OF COOLING		<input type="checkbox"/> SC <input checked="" type="checkbox"/> FC <input type="checkbox"/>			
FREQUENCY		60 Hz		RATED VOLTAGE 220 V V V	
PHASE		3 PHASE		CURRENT	
SERVICE FACTOR		1.15		NO LOAD 25.5 A A A	
INSULATION CLASS		F CLASS		FULL LOAD 62.1 A A A	
TEMP. RISE AT FULL LOAD (at S.F 1.0)				STARTING 484.8 A A A	
RES. METHOD		105		EFFICIENCY	
THERMO. METHOD				AT 1/2 LOAD %	
LOCATION		<input checked="" type="checkbox"/> INDOOR <input type="checkbox"/> OUTDOOR		AT 3/4 LOAD %	
ALTITUDE		1000 m		AT FULL LOAD 93.0 %	
HUMIDITY		80 %		POWER FACTOR	
AMBIENT TEMPERATURE		-10~40		AT 1/2 LOAD %	
RATING		<input checked="" type="checkbox"/> CONT. <input type="checkbox"/> %ED		AT 3/4 LOAD %	
NEMA DESIGN		B		AT FULL LOAD 84.0 %	
MOUNTING		<input checked="" type="checkbox"/> B3 <input type="checkbox"/> B5 <input type="checkbox"/> V1 <input type="checkbox"/> B3B5		SPEED (AT FULL LOAD) 1765 rpm	
BEARING		TYPE BALL		TORQUE	
		DEW-DE 6311ZZ/6309ZZ		FULL LOAD 10.2 kg-m 100%	
		LUBRICANT GREASE		LOCKED ROTOR 19.4 kg-m 190%	
COUPLING METHOD		<input checked="" type="checkbox"/> DIRECT <input type="checkbox"/> V-BELT		BREAKDOWN 22.5 kg-m 220%	
SHAFT				NOISE LEVEL 82.0 dB(A)	
EXTENSION		SINGLE		VIBRATION 30.0 $\mu$ m	
EXTERNAL THRUST				ALLOWABLE LOAD GD <sup>2</sup> REFERRED TO MOTOR SHAFT	
TERMINAL BOX				(AT DIRECT ON-LINE) 65.0 kg-m <sup>2</sup>	
MAIN		<input type="checkbox"/> STEEL <input type="checkbox"/> AL <input checked="" type="checkbox"/> CAST		Motor GD <sup>2</sup> 0.6545 kg-m <sup>2</sup>	
AUX.		<input type="checkbox"/> YES <input checked="" type="checkbox"/> NO		MOTOR APPROX. WEIGHT 177.0 kg	
BOX LOCATION		LEFT (Viewed from Drive end)		PAINTING MUNSELL NO. 5 PB 6/1.5	
APPLICATION STANDARDS		IEC.KS		THICKNESS <input checked="" type="checkbox"/> STANDARD <input type="checkbox"/> $\mu$ m	
ACCESSORIES (OPTIONAL)			SUBMITTAL DRAWINGS		
TEMPERATURE DETECTOR			OUTLINE DIMENSION DW-H-180M-CAT		
WINDING			S-T CURVE ST-KMH-25HC1		
TYPE			TERMINAL BOX DIMENSION TB-3040KK2003		
BEARING					
TYPE					
SPACE HEATER					
RATING					
NOTE			REMARKS		
1. THESE DATA ARE ONLY DESIGN VALUES AND SHALL BE GUARANTEED WITH TOLERANCE OF APPLICATION STANDARDS.			1. ABOVE ALL DATA ARE CALCULATED AT 100% VOLTAGE.		
2. OTHERS NOT MENTIONED IN THIS SHEET SHALL BE IN ACCORDANCE WITH OTIS STANDARD.					
FC : FAN COOLED SC : SELF COOLED			DATE PREPARED CHECKED APPROVED		
			2006-08-28 B.K.KIM J.S.PARK H.T.KIM		