

HIGEN		INDUCTION MOTOR DATA SHEET		7.5 kW - 4 P	
MODEL: I10HT1GH3		CUSTOMER :		REV. NO :	
APPLICATION:		PROJECT NAME:		QUANTITY :	
GENERAL DATA			PERFORMANCE DATA		
FRAME NO.		132M		OUTPUT 7.5 kW	
ENCLOSURE	<input type="checkbox"/> DRIP PROOF		POLES 4 POLES		
	<input checked="" type="checkbox"/> TOTALLY ENCLOSED		ROTOR TYPE SQUIRREL CAGE		
	<input type="checkbox"/> Increased Safety Exp.-proof		<input checked="" type="checkbox"/> D.O.L <input type="checkbox"/> Y- <input type="checkbox"/> REACTOR (%TAP) <input type="checkbox"/> V.V.V.F <input type="checkbox"/> SOFT-STARTER		
PROTECTION		IP 44		STARTING METHOD	
METHODS OF COOLING		<input type="checkbox"/> SC <input checked="" type="checkbox"/> FC <input type="checkbox"/>			
FREQUENCY		50 Hz		RATED VOLTAGE 220 V 380 V V	
PHASE		3 PHASE		CURRENT	
SERVICE FACTOR		1.0		NO LOAD A A A	
INSULATION CLASS		F CLASS		FULL LOAD 26.6 A 15.2 A A	
TEMP. RISE AT FULL LOAD (at S.F 1.0)				STARTING 172.9 A 98.8 A A	
RES. METHOD		105		EFFICIENCY	
THERMO. METHOD				AT 1/2 LOAD %	
LOCATION		<input checked="" type="checkbox"/> INDOOR <input type="checkbox"/> OUTDOOR		AT 3/4 LOAD %	
ALTITUDE		1000 m		AT FULL LOAD 87.5 %	
HUMIDITY		80 %		POWER FACTOR	
AMBIENT TEMPERATURE		-10~40		AT 1/2 LOAD %	
RATING		<input checked="" type="checkbox"/> CONT. <input type="checkbox"/> %ED		AT 3/4 LOAD %	
NEMA DESIGN		B		AT FULL LOAD 79.0 %	
MOUNTING		<input checked="" type="checkbox"/> B3 <input type="checkbox"/> B5 <input type="checkbox"/> V1 <input type="checkbox"/> B3B5		SPEED (AT FULL LOAD) 1450 rpm	
BEARING	TYPE		BALL		
	DEW-DE		6208ZZ/6206ZZ		
	LUBRICANT		GREASE		
COUPLING METHOD		<input checked="" type="checkbox"/> DIRECT <input type="checkbox"/> V-BELT		TORQUE	
SHAFT				FULL LOAD 4.1 kg-m 100%	
EXTENSION		SINGLE		LOCKED ROTOR 6.6 kg-m 160%	
EXTERNAL THRUST				BREAKDOWN 8.2 kg-m 200%	
TERMINAL BOX				NOISE LEVEL 77.0 dB(A)	
MAIN		<input type="checkbox"/> STEEL <input type="checkbox"/> AL <input checked="" type="checkbox"/> CAST		VIBRATION 15.0 μ m	
AUX.		<input type="checkbox"/> YES <input checked="" type="checkbox"/> NO		ALLOWABLE LOAD GD ² REFERRED TO MOTOR SHAFT (AT DIRECT ON-LINE) 29.3 kg-m ²	
BOX LOCATION		LEFT (Viewed from Drive end)		Motor GD ² 0.1060 kg-m ²	
APPLICATION STANDARDS		IEC, KS		MOTOR APPROX. WEIGHT 78.0 kg	
				PAINTING MUNSELL NO. 7.1B4.0/0.9	
				THICKNESS <input checked="" type="checkbox"/> STANDARD <input type="checkbox"/> μ m	
ACCESSORIES (OPTIONAL)			SUBMITTAL DRAWINGS		
NOTE		REMARKS			
1. THESE DATA ARE ONLY DESIGN VALUES AND SHALL BE GUARANTEED WITH TOLERANCE OF APPLICATION STANDARDS.		1. ABOVE ALL DATA ARE CALCULATED AT 100% VOLTAGE.			
2. OTHERS NOT MENTIONED IN THIS SHEET SHALL BE IN ACCORDANCE WITH OTIS STANDARD.					
FC : FAN COOLED SC : SELF COOLED		DATE	PREPARED	CHECKED	APPROVED
		2008-04-22	M.S.PARK	J.H.JO	H.J.KIM