



INDUCTION MOTOR DATA SHEET

3.7 kW 6 P 132S

MODEL: KMH-05HY8		CUSTOMER :		COIL SPEC NO.:		REV. NO : 0	
APPLICATION:		PROJECT NAME:			QUANTITY : SETS		
GENERAL DATA				PERFORMANCE DATA			
FRAME NO.		132S		OUTPUT		3.7 kW	
ENCLOSURE		☐ DRIP PROOF		POLES		6 POLES	
		☒ TOTALLY ENCLOSED		ROTOR TYPE		SQUIRREL CAGE	
		☐ Increased Safety Exp.-proof		STARTING METHOD		☒ D.O.L ☐ Y-△	
PROTECTION IP 55		☐ REACTOR (%TAP) ☐ V.V.V.F					
METHODS OF COOLING ☐ SC ☒ FC ☐ NV		☐ VECTOR-DRIVE					
PHASE		3 PHASE		RATED VOLTAGE		460 V V	
SERVICE FACTOR		1.15		FREQUENCY		60 Hz	
INSULATION CLASS		F CLASS		CURRENT			
TEMP. RISE AT FULL LOAD (at S.F 1.0)				NO LOAD		A A	
				FULL LOAD		7.0 A A	
				STARTING		45.4 A A	
RES. METHOD		105 deg		EFFICIENCY			
THERMO. METHOD		deg					
LOCATION		☒ INDOOR ☐ OUTDOOR					
ALTITUDE		1000 m		AT 1/2 LOAD		% %	
HUMIDITY		80 %		AT 3/4 LOAD		% %	
AMBIENT TEMPERATURE		-10~40 °C		AT FULL LOAD		87.5 %	
RATING		☒ CONT. ☐ %ED		POWER FACTOR			
NEMA DESIGN		B		AT 1/2 LOAD		% %	
MOUNTING		☒ B3 ☐ B5 ☐ V1 ☐ B3B5		AT 3/4 LOAD		% %	
BEARING		TYPE BALL / BALL		AT FULL LOAD		76.0 %	
		DEIN-DE 6208ZZ / 6206ZZ		SPEED (AT FULL LOAD) 1140 rpm			
		LUBRICANT GREASE		TORQUE			
COUPLING METHOD		☒ DIRECT ☐ V-BELT		FULL LOAD		3.16 kg-m 100%	
ROTATION(Facing Drive End)		☐ CW ☒ CCW		LOCKED ROTOR		4.74 kg-m 150%	
SHAFT				BREAKDOWN		6.00 kg-m 190%	
EXTENSION		SINGLE		NOISE LEVEL		65.0 dB(A)	
EXTERNAL THRUST		-		VIBRATION		30.0 μm	
TERMINAL BOX				ALLOWABLE LOAD GD ² REFERRED TO MOTOR SHAFT			
MAIN		☒ STEEL ☐ AL ☐ CAST		(AT DIRECT ON-LINE)		42.9 kg-m ²	
AUX.		☐ YES ☒ NO		Motor GD ²		0.153 kg-m ²	
BOX LOCATION		LEFT (Viewed from Drive end)		MOTOR APPROX. WEIGHT		66 kg	
APPLICATION STANDARDS		KS.IEC		PAINTING		MUNSELL NO. 5PB 2.5/8	
				THICKNESS		☒ STANDARD ☐ μm	
ACCESSORIES (OPTIONAL)				SUBMITTAL DRAWINGS			
TEMPERATURE DETECTOR				OUTLINE DIMENSION		DW-KMH-05HY8	
WINDING		NO		SPEED-TORQUE CURVE		ST-KMH-05HY8	
TYPE		-		TERMINAL BOX DIMENSION		TB-KMH-05HY8	
BEARING		NO					
TYPE		-					
SPACE HEATER		NO					
RATING		-					
NOTE				REMARKS			
1. THESE DATA ARE ONLY DESIGN VALUES AND SHALL BE GUARANTEED WITH TOLERANCE OF APPLICATION STANDARDS.				1. ABOVE ALL DATA ARE CALCULATED AT 100% VOLTAGE.			
2. OTHERS NOT MENTIONED IN THIS SHEET SHALL BE IN ACCORDANCE WITH HIGEN MOTOR STANDARD.				2. HIGH EFFICIENCY MOTOR.			
TE : TOTALLY ENCLOSED		DP : DRIP PROOF		DATE		PREPARED	
FC : FAN COOLED		SC : SELF COOLED		2016-01-27		O.S.KANG	
				CHECKED		APPROVED	
				K.I.HA		K.I.HA	