



INDUCTION MOTOR DATA SHEET

15 kW 4 P 160L

MODEL:		CUSTOMER :		COIL SPEC NO.:		REV. NO : 0	
APPLICATION:		PROJECT NAME:			QUANTITY : SETS		
GENERAL DATA				PERFORMANCE DATA			
FRAME NO.		160L		OUTPUT		15 kW	
ENCLOSURE		☐ DRIP PROOF		POLES		4 POLES	
		☒ TOTALLY ENCLOSED		ROTOR TYPE		SQUIRREL CAGE	
		☐ Increased Safety Exp.-proof		STARTING METHOD		☒ D.O.L ☐ Y- Δ	
PROTECTION		☐ REACTOR (%TAP) ☐ V.V.V.F					
METHODS OF COOLING		☐ VECTOR-DRIVE					
PHASE		3 PHASE		RATED VOLTAGE		380 V V	
SERVICE FACTOR		1.15		FREQUENCY		60 Hz	
INSULATION CLASS		F CLASS		CURRENT			
TEMP. RISE AT FULL LOAD (at S.F 1.0)				NO LOAD		A A	
				FULL LOAD		30.6 A A	
				STARTING		214.4 A A	
LOCATION		☒ INDOOR ☐ OUTDOOR		EFFICIENCY			
ALTITUDE		1000 m		AT 1/2 LOAD		% %	
HUMIDITY		80 %		AT 3/4 LOAD		% %	
AMBIENT TEMPERATURE		-10~40 $^{\circ}$ C		AT FULL LOAD		93.0 %	
RATING		☒ CONT. ☐ %ED		POWER FACTOR			
NEMA DESIGN		B		AT 1/2 LOAD		% %	
MOUNTING		☒ B3 ☐ B5 ☐ V1 ☐ B3B5		AT 3/4 LOAD		% %	
BEARING		TYPE		BALL / BALL		AT FULL LOAD	
		DEIN-DE		6309ZZC3 / 6307ZZC3		80.0 %	
		LUBRICANT		GREASE		SPEED (AT FULL LOAD)	
COUPLING METHOD		☒ DIRECT ☐ V-BELT		TORQUE		FULL LOAD	
ROTATION(Facing Drive End)		☐ CW ☒ CCW		LOCKED ROTOR		12.34 kg-m 150%	
SHAFT		EXTENSION		SINGLE		BREAKDOWN	
		EXTERNAL THRUST		-		16.46 kg-m 200%	
TERMINAL BOX		MAIN		☒ STEEL ☐ AL ☐ CAST		NOISE LEVEL	
		AUX.		☐ YES ☒ NO		82.0 dB(A)	
		BOX LOCATION		LEFT (Viewed from Drive end)		VIBRATION	
APPLICATION STANDARDS		KS.IEC		PAINTING		30.0 μ m	
				MUNSELL NO.		ALLOWABLE LOAD GD ² REFERRED TO MOTOR SHAFT	
				THICKNESS		☒ STANDARD ☐ μ m	
ACCESSORIES (OPTIONAL)				SUBMITTAL DRAWINGS			
TEMPERATURE DETECTOR				OUTLINE DIMENSION		DW-160LTFCHLS-1	
WINDING				SPEED-TORQUE CURVE		ST-P15KU1T-1	
				TERMINAL BOX DIMENSION		TB-MS180NZ-1	
SPACE HEATER							
RATING							
NOTE				REMARKS			
1. THESE DATA ARE ONLY DESIGN VALUES AND SHALL BE				1. ABOVE ALL DATA ARE CALCULATED AT 100% VOLTAGE.			
GUARANTEED WITH TOLERANCE OF APPLICATION STANDARDS.				2.PREMIUM EFFICIENCY MOTOR.			
2. OTHERS NOT MENTIONED IN THIS SHEET SHALL BE							
IN ACCORDANCE WITH HIGEN MOTOR STANDARD.							
TE : TOTALLY ENCLOSED		DP : DRIP PROOF		DATE		PREPARED	
FC : FAN COOLED		SC : SELF COOLED		2016-04-08		H.S.LIM	
				CHECKED		APPROVED	
				K.I.HA		K.I.HA	