

HIGEN		INDUCTION MOTOR DATA SHEET		90 kW 4 P 250M	
MODEL:		CUSTOMER :		REV. NO : 0	
APPLICATION:		PROJECT NAME:		QUANTITY : SETS	
GENERAL DATA			PERFORMANCE DATA		
FRAME NO.		250M		OUTPUT 90 kW	
ENCLOSURE		<input type="checkbox"/> DRIP PROOF		POLES 4 POLES	
		<input checked="" type="checkbox"/> TOTALLY ENCLOSED		ROTOR TYPE SQUIRREL CAGE	
		<input type="checkbox"/> Increased Safety Exp.-proof		<input type="checkbox"/> D.O.L <input checked="" type="checkbox"/> Y-△	
PROTECTION		IP 55		STARTING METHOD	
METHODS OF COOLING		<input type="checkbox"/> SC <input checked="" type="checkbox"/> FC <input type="checkbox"/>		<input type="checkbox"/> REACTOR (%TAP) <input type="checkbox"/> V.V.V.F	
PHASE		3 PHASE		<input type="checkbox"/> VECTOR-DRIVE	
SERVICE FACTOR		1.15		RATED VOLTAGE 440 V V	
INSULATION CLASS		F CLASS		FREQUENCY 60 Hz	
TEMP. RISE AT FULL LOAD (at S.F 1.0)		CURRENT			
RES. METHOD		105 deg		NO LOAD A A	
THERMO. METHOD		°C		FULL LOAD 145.3 A A	
LOCATION		<input checked="" type="checkbox"/> INDOOR <input type="checkbox"/> OUTDOOR		STARTING 944.5 A A	
ALTITUDE		1000 m		EFFICIENCY	
HUMIDITY		80 %		AT 1/2 LOAD %	
AMBIENT TEMPERATURE		-10~40 °C		AT 3/4 LOAD %	
RATING		<input checked="" type="checkbox"/> CONT. <input type="checkbox"/> %ED		AT FULL LOAD 94.5 %	
NEMA DESIGN		B		POWER FACTOR	
MOUNTING		<input checked="" type="checkbox"/> B3 <input type="checkbox"/> B5 <input type="checkbox"/> V1 <input type="checkbox"/> B3B5		AT 1/2 LOAD %	
BEARING		TYPE BALL / BALL		AT 3/4 LOAD %	
		DEIN-DE 6218C3 / 6314ZZC3		AT FULL LOAD 86.0 %	
		LUBRICANT GREASE		SPEED (AT FULL LOAD) 1770 rpm	
COUPLING METHOD		<input checked="" type="checkbox"/> DIRECT <input type="checkbox"/> V-BELT		TORQUE	
ROTATION(Facing Drive End)		<input type="checkbox"/> CW <input checked="" type="checkbox"/> CCW		FULL LOAD 49.5 kg-m 100%	
SHAFT		NOISE LEVEL 89.0 dB(A)			
EXTENSION		SINGLE		VIBRATION 30.0 μm	
EXTERNAL THRUST		-		ALLOWABLE LOAD GD ² REFERRED TO MOTOR SHAFT	
TERMINAL BOX		(AT DIRECT ON-LINE) 190.0 kg-m ²			
MAIN		<input checked="" type="checkbox"/> STEEL <input type="checkbox"/> AL <input type="checkbox"/> CAST		Motor GD ² 4.85 kg-m ²	
AUX.		<input type="checkbox"/> YES <input checked="" type="checkbox"/> NO		MOTOR APPROX. WEIGHT 540 kg	
BOX LOCATION		LEFT (Viewed from Drive end)		PAINTING	
APPLICATION STANDARDS		KS.IEC		MUNSELL NO. 5PB 2.5/8.0	
				THICKNESS <input checked="" type="checkbox"/> STANDARD <input type="checkbox"/> μm	
ACCESSORIES (OPTIONAL)			SUBMITTAL DRAWINGS		
TEMPERATURE DETECTOR			OUTLINE DIMENSION DW-KMH-120HV1		
WINDING NO			SPEED-TORQUE CURVE ST-KMH-120HV1		
TYPE -			TERMINAL BOX DIMENSION TB-250SM-1		
BEARING NO					
TYPE -					
SPACE HEATER NO					
RATING -					
NOTE			REMARKS		
1. THESE DATA ARE ONLY DESIGN VALUES AND SHALL BE GUARANTEED WITH TOLERANCE OF APPLICATION STANDARDS.			1. ABOVE ALL DATA ARE CALCULATED AT 100% VOLTAGE.		
2. OTHERS NOT MENTIONED IN THIS SHEET SHALL BE IN ACCORDANCE WITH HIGEN MOTOR STANDARD.			2. HIGH EFFICIENCY MOTOR.		
TE : TOTALLY ENCLOSED DP : DRIP PROOF			DATE		
FC : FAN COOLED SC : SELF COOLED			PREPARED		
			CHECKED		
			APPROVED		
			2015-06-23		
			J.H.KIM		
			S.S.YUN		
			T.I.PARK		