

HIGEN		INDUCTION MOTOR DATA SHEET		5.5 kW - 4 P	
MODEL: PMN08HK3HU		CUSTOMER :		REV. NO :	
APPLICATION:		PROJECT NAME:		QUANTITY : SETS	
GENERAL DATA			PERFORMANCE DATA		
FRAME NO.	FF265		OUTPUT	5.5 kW	7.5 HP
ENCLOSURE	<input type="checkbox"/> DRIP PROOF		POLES	2 POLES	
	<input checked="" type="checkbox"/> TOTALLY ENCLOSED		ROTOR TYPE	SQUIRREL CAGE	
	<input type="checkbox"/> Increased Safety Exp.-proof		STARTING METHOD	<input checked="" type="checkbox"/> D.O.L <input type="checkbox"/> Y-	
PROTECTION	IP 55			<input type="checkbox"/> REACTOR (%TAP) <input type="checkbox"/> V.V.V.F	
METHODS OF COOLING	<input type="checkbox"/> SC <input checked="" type="checkbox"/> FC <input type="checkbox"/>			<input type="checkbox"/> VECTOR DRIVE	
PHASE	3 PHASE		RATED VOLTAGE	220 V	380 V
SERVICE FACTOR	1.15		FREQUENCY	60 Hz	
INSULATION CLASS	F CLASS		CURRENT		
TEMP. RISE AT FULL LOAD (at S.F 1.0)			NO LOAD	A	A
RES. METHOD 105			FULL LOAD	18.4 A	10.7 A
THERMO. METHOD			STARTING	129.0 A	74.7 A
LOCATION	<input checked="" type="checkbox"/> INDOOR <input type="checkbox"/> OUTDOOR		EFFICIENCY		
ALTITUDE	1000 m		AT 1/2 LOAD %		
HUMIDITY	80 %		AT 3/4 LOAD %		
AMBIENT TEMPERATURE	-10~40		AT FULL LOAD 89.0 %		
RATING	<input checked="" type="checkbox"/> CONT. <input type="checkbox"/> %ED		POWER FACTOR		
NEMA DESIGN	B		AT 1/2 LOAD %		
MOUNTING	<input type="checkbox"/> B3 <input checked="" type="checkbox"/> B5 <input type="checkbox"/> V1 <input type="checkbox"/> B3B5		AT 3/4 LOAD %		
BEARING	TYPE	BALL	AT FULL LOAD 88.0 %		
	DEW-DE	6308ZZC3/6206ZZC3	SPEED (AT FULL LOAD) 3540 rpm		
	LUBRICANT	GREASE	TORQUE		
COUPLING METHOD	<input checked="" type="checkbox"/> DIRECT <input type="checkbox"/> V-BELT		FULL LOAD 1.51 kg-m 100%		
ROTATION(Facing Drive End)	<input type="checkbox"/> CW <input checked="" type="checkbox"/> CCW		LOCKED ROTOR 2.27 kg-m 150%		
SHAFT			BREAKDOWN 3.33 kg-m 220%		
EXTENSION SINGLE			NOISE LEVEL 83 dB(A)		
EXTERNAL THRUST			VIBRATION 30.0 μ m		
TERMINAL BOX			ALLOWABLE LOAD GD ² REFERRED TO MOTOR SHAFT		
MAIN <input type="checkbox"/> STEEL <input checked="" type="checkbox"/> AL <input type="checkbox"/> CAST			(AT DIRECT ON-LINE) 4.6 kg-m ²		
AUX. <input type="checkbox"/> YES <input checked="" type="checkbox"/> NO			Motor GD ² 0.1060 kg-m ²		
BOX LOCATION LEFT (Viewed from Drive end)			MOTOR APPROX. WEIGHT 64 kg		
APPLICATION STANDARDS KS.IEC			PAINTING	MUNSELL NO.	1.4BG 4.8/ 7.5
				THICKNESS	<input checked="" type="checkbox"/> STANDARD <input type="checkbox"/> μ m
ACCESSORIES (OPTIONAL)			SUBMITTAL DRAWINGS		
			OUTLINE DIMENSION DW-PMN08HK3HU		
			SPEED-TORQUE CURVE ST-PMN08HK3HU		
			TERMINAL BOX DIMENSION TB-3550KK3308		
NOTE			REMARKS		
1. THESE DATA ARE ONLY DESIGN VALUES AND SHALL BE			1. ABOVE ALL DATA ARE CALCULATED AT 100% VOLTAGE.		
GUARANTEED WITH TOLERANCE OF APPLICATION STANDARDS.			2. HIGH EFFICIENCY MOTOR		
2. OTHERS NOT MENTIONED IN THIS SHEET SHALL BE					
IN ACCORDANCE WITH HIGEN STANDARD.					
TE : TOTALLY ENCLOSED DP : DRIP PROOF		DATE	PREPARED	CHECKED	APPROVED
FC : FAN COOLED SC : SELF COOLED		2009-06-09	A.R.LEE	K.I.HA	H.J.KIM