

| HIGEN | | INDUCTION MOTOR DATA SHEET | | 3.7 kW 2 P 112M | |
|---|--|--|---|---|----------|
| MODEL: | | CUSTOMER : | | COIL SPEC NO.: | |
| APPLICATION: | | PROJECT NAME: | | REV. NO : 0 | |
| | | | | QUANTITY : SETS | |
| GENERAL DATA | | | PERFORMANCE DATA | | |
| FRAME NO. | | 112M | | OUTPUT 3.7 kW | |
| ENCLOSURE | | <input type="checkbox"/> DRIP PROOF | | POLES 2 POLES | |
| | | <input checked="" type="checkbox"/> TOTALLY ENCLOSED | | ROTOR TYPE SQUIRREL CAGE | |
| | | <input type="checkbox"/> Increased Safety Exp.-proof | | <input checked="" type="checkbox"/> D.O.L <input type="checkbox"/> Y- <input type="checkbox"/> REACTOR (%TAP) <input type="checkbox"/> V.V.V.F <input type="checkbox"/> VECTOR-DRIVE | |
| PROTECTION | | IP 55 | | STARTING METHOD | |
| METHODS OF COOLING | | <input type="checkbox"/> SC <input checked="" type="checkbox"/> FC <input type="checkbox"/> NV | | | |
| PHASE | | 3 PHASE | | RATED VOLTAGE 220 V 380 V | |
| SERVICE FACTOR | | 1.15 | | FREQUENCY 60 Hz | |
| INSULATION CLASS | | F CLASS | | CURRENT | |
| TEMP. RISE AT FULL LOAD (at S.F 1.0) | | | | NO LOAD A A | |
| RES. METHOD | | 80 deg | | FULL LOAD 13.3 A 7.7 A | |
| THERMO. METHOD | | deg | | STARTING 106.4 A 61.6 A | |
| LOCATION | | <input checked="" type="checkbox"/> INDOOR <input type="checkbox"/> OUTDOOR | | EFFICIENCY | |
| ALTITUDE | | 1000 m | | AT 1/2 LOAD % | |
| HUMIDITY | | 80 % | | AT 3/4 LOAD % | |
| AMBIENT TEMPERATURE | | -10~40 | | AT FULL LOAD 88.5 % | |
| RATING | | <input checked="" type="checkbox"/> CONT. <input type="checkbox"/> %ED | | POWER FACTOR | |
| NEMA DESIGN | | B | | AT 1/2 LOAD % | |
| MOUNTING | | <input checked="" type="checkbox"/> B3 <input type="checkbox"/> B5 <input type="checkbox"/> V1 <input type="checkbox"/> B3B5 | | AT 3/4 LOAD % | |
| BEARING | | TYPE BALL / BALL | | AT FULL LOAD 82.5 % | |
| DEIN-DE | | 6206ZZC3 / 6205ZZC3 | | SPEED (AT FULL LOAD) 3500 rpm | |
| LUBRICANT | | GREASE | | TORQUE | |
| COUPLING METHOD | | <input checked="" type="checkbox"/> DIRECT <input type="checkbox"/> V-BELT | | FULL LOAD 1.03 kg-m 100% | |
| ROTATION(Facing Drive End) | | <input type="checkbox"/> CW <input checked="" type="checkbox"/> CCW | | LOCKED ROTOR 1.65 kg-m 160% | |
| SHAFT | | | | BREAKDOWN 2.06 kg-m 200% | |
| EXTENSION | | SINGLE | | NOISE LEVEL 80.0 dB(A) | |
| EXTERNAL THRUST | | - | | VIBRATION 25.0 μm | |
| TERMINAL BOX | | | | ALLOWABLE LOAD GD ² REFERRED TO MOTOR SHAFT | |
| MAIN | | <input checked="" type="checkbox"/> STEEL <input type="checkbox"/> AL <input type="checkbox"/> CAST | | (AT DIRECT ON-LINE) 3.3 kg-m ² | |
| AUX. | | <input type="checkbox"/> YES <input checked="" type="checkbox"/> NO | | Motor GD ² 0.057 kg-m ² | |
| BOX LOCATION | | LEFT (Viewed from Drive end) | | MOTOR APPROX. WEIGHT 45 kg | |
| APPLICATION STANDARDS | | KS.IEC | | PAINTING | |
| | | | | MUNSELL NO. 5PB 2.5/8 | |
| | | | | THICKNESS <input checked="" type="checkbox"/> STANDARD <input type="checkbox"/> μm | |
| ACCESSORIES (OPTIONAL) | | | SUBMITTAL DRAWINGS | | |
| TEMPERATURE DETECTOR | | | OUTLINE DIMENSION DW-112MTFCHLS-5 | | |
| WINDING | | | SPEED-TORQUE CURVE ST-P3.7KK3T112M-1 | | |
| TYPE | | | TERMINAL BOX DIMENSION TB-MS112NZ-1 | | |
| BEARING | | | | | |
| TYPE | | | | | |
| SPACE HEATER | | | | | |
| RATING | | | | | |
| | | | | | |
| NOTE | | | REMARKS | | |
| 1. THESE DATA ARE ONLY DESIGN VALUES AND SHALL BE | | | 1. ABOVE ALL DATA ARE CALCULATED AT 100% VOLTAGE. | | |
| GUARANTEED WITH TOLERANCE OF APPLICATION STANDARDS. | | | 2. PREMIUM EFFICIENCY MOTOR. (IE3) | | |
| 2. OTHERS NOT MENTIONED IN THIS SHEET SHALL BE | | | | | |
| IN ACCORDANCE WITH HIGEN MOTOR STANDARD. | | | | | |
| TE : TOTALLY ENCLOSED | | DP : DRIP PROOF | | DATE | PREPARED |
| FC : FAN COOLED | | SC : SELF COOLED | | 2016-04-07 | S.D.YUN |
| | | | | CHECKED | APPROVED |
| | | | | S.D.YUN | K.I.HA |