

HIGEN		INDUCTION MOTOR DATA SHEET		2.2 kW 6 P 112M	
MODEL: KMH-03HK8		CUSTOMER :		COIL SPEC NO.:	
APPLICATION:		PROJECT NAME:		REV. NO : 0	
				QUANTITY : SETS	
GENERAL DATA			PERFORMANCE DATA		
FRAME NO.		112M		OUTPUT 2.2 kW	
ENCLOSURE		☐ DRIP PROOF		POLES 6 POLES	
		☒ TOTALLY ENCLOSED		ROTOR TYPE SQUIRREL CAGE	
		☐ Increased Safety Exp.-proof		☒ D.O.L ☐ Y- ☐ REACTOR (%TAP) ☐ V.V.V.F ☐ VECTOR-DRIVE	
PROTECTION		IP 55		STARTING METHOD	
METHODS OF COOLING		☐ SC ☒ FC ☐ NV			
PHASE		3 PHASE		RATED VOLTAGE 220 V 380 V	
SERVICE FACTOR		1.15		FREQUENCY 60 Hz	
INSULATION CLASS		F CLASS		CURRENT	
TEMP. RISE AT FULL LOAD (at S.F 1.0)				NO LOAD A A	
RES. METHOD		105		FULL LOAD 9.3 A 5.4 A	
THERMO. METHOD				STARTING 55.8 A 32.3 A	
LOCATION		☒ INDOOR ☐ OUTDOOR		EFFICIENCY	
ALTITUDE		1000 m		AT 1/2 LOAD %	
HUMIDITY		80 %		AT 3/4 LOAD %	
AMBIENT TEMPERATURE		-10~40		AT FULL LOAD 87.5 %	
RATING		☒ CONT. ☐ %ED		POWER FACTOR	
NEMA DESIGN		B		AT 1/2 LOAD %	
MOUNTING		☒ B3 ☐ B5 ☐ V1 ☐ B3B5		AT 3/4 LOAD %	
BEARING		TYPE BALL / BALL		AT FULL LOAD 71.0 %	
		DEIN-DE 6206ZZ / 6205ZZ		SPEED (AT FULL LOAD) 1150 rpm	
		LUBRICANT GREASE		TORQUE	
COUPLING METHOD		☒ DIRECT ☐ V-BELT		FULL LOAD 1.86 kg-m 100%	
ROTATION(Facing Drive End)		☐ CW ☒ CCW		LOCKED ROTOR 2.98 kg-m 160%	
SHAFT				BREAKDOWN 3.54 kg-m 190%	
EXTENSION		SINGLE		NOISE LEVEL 63.0 dB(A)	
EXTERNAL THRUST		-		VIBRATION 30.0 μm	
TERMINAL BOX				ALLOWABLE LOAD GD ² REFERRED TO MOTOR SHAFT	
MAIN		☒ STEEL ☐ AL ☐ CAST		(AT DIRECT ON-LINE) 29.3 kg-m ²	
AUX.		☐ YES ☒ NO		Motor GD ² 0.058 kg-m ²	
BOX LOCATION		LEFT (Viewed from Drive end)		MOTOR APPROX. WEIGHT 41 kg	
APPLICATION STANDARDS		KS.IEC		PAINTING	
				MUNSELL NO. 5PB 2.5 / 8	
				THICKNESS ☒ STANDARD ☐ μm	
ACCESSORIES (OPTIONAL)			SUBMITTAL DRAWINGS		
TEMPERATURE DETECTOR			OUTLINE DIMENSION DW-KMH-03HK8		
WINDING			TERMINAL BOX DIMENSION TB-KMH-03HK8		
TYPE			SPEED-TORQUE CURVE ST-KMH-03HK8		
BEARING					
TYPE					
SPACE HEATER					
RATING					
NOTE			REMARKS		
1. THESE DATA ARE ONLY DESIGN VALUES AND SHALL BE GUARANTEED WITH TOLERANCE OF APPLICATION STANDARDS.			1. ABOVE ALL DATA ARE CALCULATED AT 100% VOLTAGE.		
2. OTHERS NOT MENTIONED IN THIS SHEET SHALL BE IN ACCORDANCE WITH HIGEN MOTOR STANDARD.			2. HIGH EFFICIENCY MOTOR.		
TE : TOTALLY ENCLOSED DP : DRIP PROOF			DATE		
FC : FAN COOLED SC : SELF COOLED			PREPARED		
			CHECKED		
			APPROVED		
			2015-07-13		
			S.D.YUN		
			S.D.YUN		
			K.I.HA		