

HIGEN		INDUCTION MOTOR DATA SHEET		40 HP - 2 P	
MODEL: I40HU3FHIG		CUSTOMER :		REV. NO : 0	
APPLICATION:		PROJECT NAME:		QUANTITY : SETS	
GENERAL DATA			PERFORMANCE DATA		
FRAME NO.		FF350		OUTPUT 30 kW 40 HP	
ENCLOSURE		<input type="checkbox"/> DRIP PROOF		POLES 2 POLES	
		<input checked="" type="checkbox"/> TOTALLY ENCLOSED		ROTOR TYPE SQUIRREL CAGE	
		<input type="checkbox"/> Increased Safety Exp.-proof		<input type="checkbox"/> D.O.L <input checked="" type="checkbox"/> Y-	
PROTECTION		IP 54		<input type="checkbox"/> REACTOR (%TAP) <input type="checkbox"/> V.V.V.F	
METHODS OF COOLING		<input type="checkbox"/> SC <input checked="" type="checkbox"/> FC <input type="checkbox"/>		<input type="checkbox"/> SOFT-STARTER	
PHASE		3 PHASE		RATED VOLTAGE 380 V V V	
SERVICE FACTOR		1.15		FREQUENCY 60 Hz	
INSULATION CLASS		F CLASS		CURRENT	
TEMP. RISE AT FULL LOAD (at S.F 1.0)				NO LOAD 20.0 A A A	
RES. METHOD		105		FULL LOAD 59.2 A A A	
THERMO. METHOD				STARTING 506.1 A A A	
LOCATION		<input checked="" type="checkbox"/> INDOOR <input type="checkbox"/> OUTDOOR		EFFICIENCY	
ALTITUDE		1000 m		AT 1/2 LOAD %	
HUMIDITY		90 %		AT 3/4 LOAD %	
AMBIENT TEMPERATURE		-10-40		AT FULL LOAD 91.7 %	
RATING		<input checked="" type="checkbox"/> CONT. <input type="checkbox"/> %ED		POWER FACTOR	
NEMA DESIGN		B		AT 1/2 LOAD %	
MOUNTING		<input type="checkbox"/> B3 <input type="checkbox"/> B5 <input checked="" type="checkbox"/> V1 <input type="checkbox"/> B3B5		AT 3/4 LOAD %	
BEARING		TYPE BALL		AT FULL LOAD 84.0 %	
		DEW-DE 6312ZZC3/6309ZZ		SPEED (AT FULL LOAD) 3546 rpm	
		LUBRICANT GREASE		TORQUE	
COUPLING METHOD		<input checked="" type="checkbox"/> DIRECT <input type="checkbox"/> V-BELT		FULL LOAD 8.2 kg-m 100%	
ROTATION(Facing Drive End)		<input checked="" type="checkbox"/> CW <input checked="" type="checkbox"/> CCW		LOCKED ROTOR 10.7 kg-m 130%	
SHAFT				BREAKDOWN 15.7 kg-m 190%	
EXTENSION		SINGLE		NOISE LEVEL 91.0 dB(A)	
EXTERNAL THRUST				VIBRATION 25.0 μm	
TERMINAL BOX				ALLOWABLE LOAD GD ² REFERRED TO MOTOR SHAFT	
MAIN		<input type="checkbox"/> STEEL <input type="checkbox"/> AL <input checked="" type="checkbox"/> CAST		(AT DIRECT ON-LINE) 16.3 kg-m ²	
AUX.		<input type="checkbox"/> YES <input checked="" type="checkbox"/> NO		Motor GD ² 0.5309 kg-m ²	
BOX LOCATION		LEFT (Viewed from Drive end)		MOTOR APPROX. WEIGHT 260.0 kg	
APPLICATION STANDARDS		IEC.KS		PAINTING	
				MUNSELL NO. 5PB 8/2.5	
				THICKNESS <input checked="" type="checkbox"/> STANDARD <input type="checkbox"/> μm	
ACCESSORIES (OPTIONAL)			SUBMITTAL DRAWINGS		
TEMPERATURE DETECTOR			OUTLINE DIMENSION		
WINDING			Speed Vs Torque Curve		
TYPE					
BEARING					
TYPE					
SPACE HEATER					
RATING					
NOTE			REMARKS		
1. THESE DATA ARE ONLY DESIGN VALUES AND SHALL BE GUARANTEED WITH TOLERANCE OF APPLICATION STANDARDS.			1. ABOVE ALL DATA ARE CALCULATED AT 100% VOLTAGE.		
2. OTHERS NOT MENTIONED IN THIS SHEET SHALL BE IN ACCORDANCE WITH OTIS STANDARD.					
TE : TOTALLY ENCLOSED		DP : DRIP PROOF		DATE	PREPARED
FC : FAN COOLED		SC : SELF COOLED		2006-08-17	B.K.KIM
				CHECKED	APPROVED
				J.S.PARK	H.T.KIM